



DIGITALPRESSUREFOLIE, SPECIALLY FOR SUBLIMATION-DYED POLYESTER TEXTILES

Digital printable and plottable white polyurethane film, specially developed for printing on sublimation-dyed polyester textiles. It has a barrier layer that prevents the sublimation dyes from penetrating your motif.



AVAILABLE IN

- 50 cm x 25 m roll

RECOMMENDED FABRICS * Test before application!

- 100% Sublimation-dyed polyester*
- 100% Polyester-Cotton blends
- Softshell*

CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. Cutting too deep will cause difficulties when weeding or pressing.

APPLICATION INSTRUCTIONS

Temperature: 140° C
Time: 10 sec.
Pressure: Medium (#4-6 with Hotronix®)
Carrier: Hot-warm peel

ACCESSORIES RECOMMENDED

- CAD-COLOR® MagicMask® High Tack
- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers
- Squeegee

CARE INSTRUCTIONS

Washable up to 40° C. Please do not use fabric softener or bleach. Suitable for tumble drying on a gentle setting. Wash and iron inside out.

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

