



HOME OFFICE

PO Box 1605
5409 Hamlet Drive
Findlay, Ohio 45840-1605 USA
inquiries@rowmark.com

EUROPE OFFICE/WAREHOUSE

Schaarbeekstraat 44
9120 Beveren-Waas
Belgium
+32 (0)3 870 41 10
emea@rowmark.com

TECHNICAL SUPPORT

877.769.6275 /// 419.425.8974
techhelp@rowmark.com

CUSTOM REQUESTS

800.243.3339 /// 419.425.2407
customerservice@rowmark.com

877.rowmark / rowmark.com



Engage. Interact. Share.



Impress with Reverse LaserMark®

Specially designed for the laser engraver, this line has a clear, non-glare matte finish over a layer of rich color. It offers a crisp, clean image and ultra-fine laser lettering, with a durable surface that resists fingerprints.

Achieve special effects with reverse engraving and backpainting. Reverse LaserMark® will help you make your best impression.



Reverse LaserMark



REVERSE LASERMARK®



Matte/Red 922-601 2-ply 1/16"	Matte/Burgundy 922-621 2-ply 1/16"	Matte/Ribbon Pink 922-661 2-ply 1/16"	Matte/Yellow 922-701 2-ply 1/16"	Matte/Bright Green 922-931 2-ply 1/16"	Matte/Blue 922-511 2-ply 1/16"	Matte/Navy Blue 922-551 2-ply 1/16"	Matte/White 922-201 2-ply 1/16"	Matte/Ivory 922-221 2-ply 1/16"	Matte/Dark Brown 922-841 2-ply 1/16"
Matte/Black 922-401 2-ply 1/16"	Matte/Smooth Gold* 922-711 2-ply 1/16" 942-711 2-ply 1/8"	Gloss/Smooth Gold* 922-710 2-ply 1/16" 942-710 2-ply 1/8"	Matte/Smooth Silver* 922-341 2-ply 1/16" 942-341 2-ply 1/8"	Gloss/Smooth Silver* 922-340 2-ply 1/16" 942-340 2-ply 1/8"	Matte/Clear 311-101 1-ply 1/32" 322-101 1-ply 1/16" 342-101 1-ply 1/8"	Clear/Clear 411-100 1-ply 1/32" 422-100 1-ply 1/16" 442-100 1-ply 1/8"			

REVERSE LASERMARK® TECHNICAL SPECIFICATIONS

Material Microsurfaced impact acrylic for reverse engraving	Sheet Size 24-1/8" x 48-3/4" // 613mm x 1238mm	Usage ADA Compliant/Tactile Signage Exterior Signage Interior Signage Illuminated Wayfinding Personal Identification	Capabilities Back-lighting Bevels Bonds Drills Heat Bendable Hot Stamps Saws Screen Prints Laser Vector Cuts Shears (works on thicknesses 1/16" & under) Permits Fine Detail Engraving
Finish Matte non-glare Gloss ■	Engraving Depth .003" // 0.08mm		

*Some LaserMark® Reverse foils are not recommended for applications in which UV stability is a requirement.

